

NEW COMBUSTIBLE GAS LEAK DETECTOR NEW CD100A

CD100A

The CD100A is designed to detect combustible gas leaks in residential and small commercial applications. It is small, easy to use and has a 18" long flexible gooseneck for hard to reach areas.

- Simple adjustable tick rate increases as the sensor tip approaches a leak
- Audio and visual tick rate, fully adjustable
- Easy one hand operation
- Long 18" (45cm) gooseneck for hard to reach areas
- 'Tip light' in sensor cover illuminates the area of the leak
- Rubber boot protects instrument
- Sensor provides accurate detection
- Headphone jack
- Separate battery compartment for quick and easy battery replacement

Partial list of gases sensed:

Acetone, Alcohol, Ammonia, Benzene, Butane, Gasoline, Halon, Hydrogen Sulfide, Industrial Solvents, Jet Fuel, Laquer Thinners, Methane, Naphta, Natural Gas, Propane, Refrigerants, Toluene ... and more



SPECIFICATIONS

Power Supply	9V Alkaline battery
Battery life	5 hours typical use
Sensor	Solid state semiconductor
Sensitivity	50 ppm
Dimensions	8" x 4" x 1.5" (200x100x38 mm)
Gooseneck	18" (450mm)
Tick adjustment	Fully adjustable thumbwheel
Tick indication	Flashing LED

ACCESSORIES

Replacement Sensor
Replacement Sensor Cap
Headphones
Hard Carrying Case